14" Crescent Ice Maker • ADA Series







FEATURES & BENEFITS

PERFORMANCE

- Uses less than 3 gallons of water to produce up to 23 lbs of ice per day
- Up to 12 lbs in ice storage capacity
- Daily ice production rate is approx. 4 times greater than the average household refrigerator
- Crescent ice cube dimensions: $^{1}/_{2}''$ W x $^{3}/_{4}''$ H x 2 $^{1}/_{4}''$ L
- On/Off switch is conveniently located on the grille

INTERIOR/EXTERIOR

• No drain required

• Door swing is field reversible, and is shipped right-hand hinged

INTEGRATION

• Unit is designed to be built-in or can be freestanding

- Accepts a 1/4" custom insert panel
- Available in the following finishes: Black or White

MODEL DETAILS


Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
U-BI95B-00A	115 / 60	Field Reversible	Black Solid	59 lb
U-BI95W-00A	115 / 60	Field Reversible	White Solid	59 lb

ACCESSORIES


Model	Description	Finish	Shipping Weight
ULAWATERHOOKUP	Braided Water Supply Line Kit	N/A	2 lb

DIMENSIONS

Dimensions shown apply to all finishes.



CABINET CUT-OUT



INSTALLATION NOTES

No additional clearance around sides, top or rear of unit is needed for ventilation.

Do not obstruct front grille air flow.

SPECIFICATIONS

Model	BI95	
Amps: Running	2.5	
Control Type	On/Off Switch	
Defrost Type	Manual	
Dimensions: Product Depth	17" / 432 mm	
Dimensions: Product Height	25 ¹ / ₁₆ " / 637 mm	
Dimensions: Product Width	13 ¹⁵ / ₁₆ " / 354 mm	
Energy Consumption: Avg. Per Year	N/A	
Panel Type	Insert	
Panel Thickness	½" (6.3 mm)	
Panel Height	13 ¹⁵ / ₃₂ " (342 mm)	
Panel Width	12 ¹⁵ / ₁₆ " (329 mm)	
ENERGY STAR	N/A	
Ice Production Per Day	23 lb	
Ice Storage	12 lb	
Product Weight: Max	53 lb	
Refrigerant Type	R134a	
Sabbath (Star K Certified)	No	

ELECTRICAL REQUIREMENTS

This unit requires a grounded, polarized 115 VAC, 60 Hz, 15 A power supply (normal household current).





Please visit u-line.com to view this model's User Guide & Service Manual. All Specifications are subject to change without notice.